

Reference

- Axelrod, A., He, X., and Gao, J. (2011). Domain adaptation via pseudo in-domain data selection. In *Proceedings of the conference on empirical methods in natural language processing*, pages 355–362. Association for Computational Linguistics.
- Banarescu, L., Bonial, C., Cai, S., Georgescu, M., Griffitt, K., Hermjakob, U., Knight, K., Koehn, P., Palmer, M., and Schneider, N. (2013). Abstract meaning representation for sembanking. In *Proceedings of the 7th Linguistic Annotation Workshop and Interoperability with Discourse*, pages 178–186.
- Bangalore, S. and Rambow, O. (2000). Using tags, a tree model, and a language model for generation. In *Proceedings of the Fifth International Workshop on Tree Adjoining Grammar and Related Frameworks (TAG+5)*, pages 33–40.
- Bateman, J. A. (1997). Enabling technology for multilingual natural language generation: the kpml development environment. *Natural Language Engineering*, 3(1):15–55.
- Belz, A. (2008). Automatic generation of weather forecast texts using comprehensive probabilistic generation-space models. *Natural Language Engineering*, 14(4):431–455.
- Bojar, O., Chatterjee, R., Christian, F., Yvette, G., Barry, H., Matthias, H., Philipp, K., Qun, L., Varvara, L., Christof, M., et al. (2017). Findings of the 2017 conference on machine translation (wmt17). In *Second Conference on Machine Translation*, pages 169–214. The Association for Computational Linguistics.
- Bojar, O., Chatterjee, R., Federmann, C., Graham, Y., Haddow, B., Huck, M., Yepes, A. J., Koehn, P., Logacheva, V., Monz, C., et al. (2016). Findings of the 2016 conference on machine translation. In *Proceedings of the First Conference on Machine Translation: Volume 2, Shared Task Papers*, pages 131–198.
- Chen, Z., Eavani, H., Chen, W., Liu, Y., and Wang, W. Y. (2019). Few-shot nlg with pre-trained language model. *arXiv:1904.09521 [cs]*. arXiv:1904.09521.
- Dethlefs, N. (2017). Domain transfer for deep natural language generation from abstract meaning representations. *IEEE Computational Intelligence Magazine*, 12(3):18–28.
- Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2019). Bert: Pre-training of deep bidirectional transformers for language understanding.

- In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186.
- Duboue, P. A. and McKeown, K. R. (2003). Statistical acquisition of content selection rules for natural language generation. In *Proceedings of the 2003 conference on Empirical methods in natural language processing*, pages 121–128. Association for Computational Linguistics.
- Dušek, O. and Jurčiček, F. (2015). Training a natural language generator from unaligned data. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 451–461.
- Dušek, O. and Jurčiček, F. (2019). Neural generation for czech: Data and baselines. In *Proceedings of the 12th International Conference on Natural Language Generation, Tokyo, Japan*.
- Dušek, O., Sevegnani, K., Konstas, I., and Rieser, V. (2019). Automatic quality estimation for natural language generation: Ranting (jointly rating and ranking). In *Proceedings of the 12th International Conference on Natural Language Generation, Tokyo, Japan*.
- Gatt, A. and Kraemer, E. (2018). Survey of the state of the art in natural language generation: Core tasks, applications and evaluation. *Journal of Artificial Intelligence Research*, 61:65–170.
- Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, 9(8):1735–1780.
- Lampouras, G. and Vlachos, A. (2016). Imitation learning for language generation from unaligned data. In *Proceedings of COLING 2016, the 26th International Conference on Computational Linguistics: Technical Papers*, pages 1101–1112.
- Lavie, A. and Agarwal, A. (2007). Meteor: An automatic metric for mt evaluation with high levels of correlation with human judgments. In *Proceedings of the Second Workshop on Statistical Machine Translation*, pages 228–231. Association for Computational Linguistics.
- Lin, C.-Y. (2004). ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.
- Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., and Stoyanov, V. (2019). Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

- McRoy, S. W., Channarukul, S., and Ali, S. S. (2003). An augmented template-based approach to text realization. *Natural Language Engineering*, 9(4):381–420.
- Mi, F., Huang, M., Zhang, J., and Faltings, B. (2019). Meta-learning for low-resource natural language generation in task-oriented dialogue systems. *arXiv:1905.05644 [cs]*. arXiv: 1905.05644.
- Moore, R. C. and Lewis, W. (2010). Intelligent selection of language model training data. In *Proceedings of the ACL 2010 conference short papers*, pages 220–224. Association for Computational Linguistics.
- Novikova, J., Dušek, O., Curry, A. C., and Rieser, V. (2017). Why we need new evaluation metrics for nlg. *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, page 2231–2240. arXiv: 1707.06875.
- Oremus, W. (2014). The First News Report on the L.A. Earthquake Was Written by a Robot. <https://goo.gl/jeHRPX>.
- Papineni, K., Roukos, S., Ward, T., and Zhu, W.-J. (2002). Bleu: A method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics, ACL '02*, pages 311–318, Stroudsburg, PA, USA. Association for Computational Linguistics.
- Peters, M. E., Neumann, M., Iyyer, M., Gardner, M., Clark, C., Lee, K., and Zettlemoyer, L. (2018). Deep contextualized word representations. In *Proceedings of NAACL-HLT*, pages 2227–2237.
- Portet, F., Reiter, E., Gatt, A., Hunter, J., Sripada, S., Freer, Y., and Sykes, C. (2009). Automatic generation of textual summaries from neonatal intensive care data. *Artificial Intelligence*, 173(7–8):789–816.
- Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., and Sutskever, I. (2019). Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8).
- Reiter, E. and Dale, R. (2000). *Building natural language generation systems*. Cambridge university press.
- Reiter, E., Mellish, C., and Levine, J. (1995). Automatic generation of technical documentation. *Applied Artificial Intelligence an International Journal*, 9(3):259–287.
- Rumelhart, D. E., Hinton, G. E., Williams, R. J., et al. (1988). Learning representations by back-propagating errors. *Cognitive modeling*, 5(3):1.

- Sun, S., Cheng, Y., Gan, Z., and Liu, J. (2019). Patient knowledge distillation for bert model compression. *arXiv preprint arXiv:1908.09355*.
- Sutskever, I., Vinyals, O., and Le, Q. V. (2014). Sequence to sequence learning with neural networks. In *Advances in neural information processing systems*, pages 3104–3112.
- Tran, V.-K. and Nguyen, L.-M. (2018). Adversarial domain adaptation for variational neural language generation in dialogue systems. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 1205–1217.
- Tseng, B.-H., Budzianowski, P., Wu, Y.-c., and Gasic, M. (2019). Tree-structured semantic encoder with knowledge sharing for domain adaptation in natural language generation. In *Proceedings of the 20th Annual SIGdial Meeting on Discourse and Dialogue*, pages 155–164.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.
- Walker, M. A., Stent, A., Mairesse, F., and Prasad, R. (2007). Individual and domain adaptation in sentence planning for dialogue. *Journal of Artificial Intelligence Research*, 30:413–456.
- Wen, T.-H., Gašić, M., Mrkšić, N., Rojas-Barahona, L. M., Su, P.-H., Vandyke, D., and Young, S. (2016). Multi-domain neural network language generation for spoken dialogue systems. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 120–129, San Diego, California. Association for Computational Linguistics.